

# **UM3E Series**

As an Ultra HD large display, the UM3E series delivers content in a fine detail with vivid colors enough to captivate numerous viewers. Equipped with high compatibility and intuitive user interface, the product allows you to easily connect and coordinate other devices or to manage content in a meeting room or in retail stores.





# **UM3E** Series

# **Superior Picture Quality**



### **True Color, Immersive View**

The UM3E series is large enough to display content and get undivided attention from various viewers. LG IPS panel features a wide range of angle to deliver clear content regardless of the position of viewers. Each pixel in the IPS panel reproduces image colors true-to-life, without distortion.



#### Vivid Color Details with Ultra HD

The UHD resolution allows users to view details even when zooming in on the display, with four times higher definition than FHD. The UL3E ensures stable UHD video playback with HEVC (High Efficiency Video Coding).





# **UM3E** Series

### Powerful webOS Smart Signage Platform




### **Easy Content Management**

The embedded CMS (Content Management System) allows you to create and edit content using internal/external sources as well as set playlists to play at the desired schedule without the need for a separate PC. Thanks to the intuitive GUI and a menu structure based on usage scenarios, content management has been made much easier.



### Simple Group Management

The embedded Group Manager makes a master display work as a server and manage other displays <sup>1</sup> connected on the same network. This way you can group and control multiple displays in your place of business and distribute playlists to them all at once, using input devices such as a remote control.



1) One master display can create a max. of 25 groups, and each group can consist of a max. of 12 slave displays.

# **UM3E** Series

### Powerful webOS Smart Signage Platform



### **Various Sensor Applications**

LG webOS smart signage platform easily supports connections with external sensors such as GPIO, NFC/RFID, temperature sensors, etc. via USB plug-in. The overall cost of ownership is more affordable because no need to purchase additional software or media players for creating value-added solutions.





#### Multi Screen Mode

PBP (Picture-By-Picture) features multi screen in a single display with up to 4 input sources while PIP (Picture-In-Picture) supports playing both main screen and sub screen at the same time with various layouts. This gives great flexibility to allocate space for each content souce.



# **UM3E** Series

### **Wireless Solution**



### **Content Sharing**

Content Mirroring among devices is more convenient on a Wi-Fi network.



### **Real-time Promotion**

With Beacon and BLE (Bluetooth Low Energy), shop managers can provide coupons and information in real-time.



### **Wireless Access Point**

The UM3E series operates as a virtual router which can be an wireless access point for mobile devices.





# **UM3E** Series

# **High Compatibility**



### Compatibility with AV Control System

The UM3E series has been certified Crestron Connected® for a higher level of compatibility with professional AV controls to achieve seamless integration and automated control <sup>1)</sup>, boosting business management efficiency.



#### 1) Network based control

### Compatibility with Video Conference System


For the optimum visual meeting, the UM3E has certified its compatibility with Cisco Spark Room Kits, a system that offers powerful and integrated control<sup>1</sup> for a smarter video conference, eliminating a waste of time to set up the picture quality or to change input on incoming calls.



1) The integrated control of the display and Cisco system is enabled through the HDMI cable connection.


### **Dimensions**


86" 75"



# **Connectivity**

86" 75"





<sup>\*</sup> Dimensions & Jack Panels (Read/Side) may differ from the above image, so please contact LG salesteam to verify before ordering.

		-					
	2	. ***	C 3	٠.		n	-
_	Ut	 	ca	LI	U	1112	3
_	_	 			_		_

86UM3E 75UM3E

	MODEL		86UM3E	75UM3E	
	Screen Si		86	75	
	Panel Tec		IPS	IPS	
	Back Ligh		Edge	Edge	
	Aspect R		16:9	16:9	
	Native Re		3840 x 2160 (UHD)	3840 x 2160 (UHD)	
	Refresh F		240Hz	120Hz	
		ss (Typical)	350 nits	350 nits	
	Contrast		1,200:1	1,200:1	
PANEL	Dynamic CR		500,000:1	2,000,000:1 (DTV Label only)	
	Color gamut		NTSC: 72%	NTSC: 72%	
	Viewing Angle (H x V)		178° x 178°	178° x 178°	
	Color Depth		10BIT, 1.07 Billion	10BIT, 1.06 Billion	
	Response Time (G to G)		8 ms	6 ms	
		reatment (Haze)	Haze 3%	Haze 3%	
	Life time		30,000 Hrs	50,000 Hrs	
	Operation		16 Hrs	24 Hrs	
	Orientati		Landscape	Portrait & Landscape	
	Overlay T	ouch Compatibility	No	Yes	
		HDMI	Yes (3), HDCP2.2	Yes (3), HDCP2.2	
	Digital	DP	Yes (1), HDCP1.3	Yes (1), HDCP1.3	
		DVI-D	Yes (1)	Yes (1)	
	Analog	RGB	No	No	
	Audio In		Yes (1)	Yes (1)	
NPUT	External	RS232C IN	Yes (1)	Yes (1)	
	Control	RJ45(LAN)	Yes (1)	Yes (1)	
		IR IN	Yes (1)	Yes (1)	
	Pixel Sen	sor	No	No	
	USB		Yes (2), USB2.0	Yes (2), USB2.0	
	SD Card(	SDHC/Full Size)	No	No	
	HDMI Ou	t	No	No	
	DP Out		Yes (1)	Yes (1)	
VITDUT	Audio Ou	t	Yes (1, Off/Fixed/Variable)	Yes (1, Off/Fixed/Variable)	
UTPUT	Externel Speaker Out		No	No	
	External RS232C OUT		Yes (3.5mm)	Yes (3.5mm)	
	Control RJ45(LAN)		No	No	
	Bezel Color		Black	Black	
	Bezel Wie	dth (On Bezel)	15.6 mm (On) / 14.3 mm (Off)	15.9 mm (On) / 14.9 mm (Off)	
	Monitor I	Dimensions	"1926.2mm x 1097.2mm x 60.6mm	"1682.4mm x 960.3mm x 57.9mm	
	(W x H x D)		(without handle) "	(without handle, without LG logo)"	
MECHANICAL PECIFICATION	Weight(Head)		49 kg	41.5 kg	
FECIFICATION	Carton Dimensions (W x H x D)		2073mm x 1260mm x 292mm	1816mm x 1123mm x 228mm	
	Packed V	Veight	61.1 kg	49 kg	
	Handle		Yes	Yes	
	VESATM Standard Mount Interface		600 x 400	600 x 400	
	Internal Memory		8GB (System 4GB + Available 3.6GB)	8GB (System 4GB + Available 3.6GB)	
	Wi-Fi Bui		Yes	Yes	
		Temperature Sensor	Yes	Yes	
ARDWARE	Sensors	Auto Brightness sensor	Yes	Yes	
		Current Sensor	Yes	Yes	
	Local Key	Operation	Yes	Yes	
DUND	Speaker		Built in	Built in	
	Safety		IEC 60950-1 / EN 60950-1 / UL 60950-1	IEC 60950-1 / EN 60950-1 / UL 60950-	
CERTIFICATION	EMC		FCC Class "A" / CE / KC	FCC Class "A" / CE / KC	
	ErP / Energy Star		NA/NA	NA/EPA7.0	
Media Player Compatibility	OPS type compatible		Yes	Yes	
	External Media player Attatchable		Yes	Yes	
anguage	English, French, German, Spanish, Italian, Korean , Chinese(Simplified), Chinese(Original), Languages Portugues(Brazil), Swedish, Finnish, Norvegian, Daish, Russian, Japanese, Portugues(Europ Dutch, Czech, Greek				

86UM3E	75UM3E
OUUNISE	/30W3E

	webOS ver.		webOS 4.0	webOS 4.0	
		USB Auto Playback Local Contents	Yes	Yes	
	Embedded CMS	Scheduling	Yes	Yes	
		Group Manager	Yes	Yes	
	Fail over		Yes	Yes	
	Image	Booting Logo	Yes	Yes	
	Customization	No Signal	Yes	Yes	
		RS-232C	Yes	Yes	
	Content Sync.	Local Network	Yes	Yes	
		PIP	Yes	Yes	
	Multi-screen				
		PBP	Yes (4)	Yes (4)	
	Screen Share		Yes	Yes	
	Video Tag		Yes (2)	Yes (2)	
	Play via URL		Yes	Yes	
	OSD Rotation		Yes	Yes	
	Lock mode		Yes	Yes	
	Content Rotation		Yes Yes	Yes Yes	
	Gapless Playback Tile Mode Setting		Yes (Max. 15x15)	Yes (Max. 15x15)	
	Setting Data Cloning		Yes	Yes	
	Firmware Update		Yes	Yes	
ware	SNMP	by receivers.	Yes (Ver. 1.4)	Yes (Ver. 1.4)	
	ISM Mode (Image	Sticking	Yes	Yes	
	Minimization)				
	Auto Set ID		Yes	Yes	
	Status Mailing		Yes	Yes	
	Control Manager	C	Yes	Yes	
	3rd Party	Crestron Connected	Yes	Yes	
		DPM	Yes	Yes	
		On/Off Schedule	Yes	Yes	
		Holiday Schedule	Yes	Yes	
		Power on Status	Standby, PWR, LST	Standby, PWR, LST	
	Power		21 1		
	Mg+B83:B97mt.		Yes	Yes	
		Smart Energy Saving	Yes	Yes	
		PM mode	Yes	Yes	
		Wake on LAN	Yes	Yes	
		Power on Delay	Yes	Yes	
	Daylight Saving T		Yes	Yes	
	Beacon		Yes	Yes	
	HDMI-CEC		Yes	Yes	
	SI Server Setting		Yes	Yes	
webRTC			Yes 10485 ( 086 to 4086	Yes 10495 (095 to 4095	
onment itions	Operation Temperature Operation Humidity		32°F to 104°F / 0°C to 40°C 10% to 80%	32°F to 104°F / 0°C to 40°C 10% to 80%	
100113		icy	100-240V~, 50/60Hz		
	Power Supply			100-240V~, 50/60Hz	
	Power Type		Built-In Power	Built-In Power	
TRICAL	Power (Max)		315 W 345 W	160 W 185 W	
icric	Power (Max) Smart Enegy Saving		220.5 W	112 W	
	DPM		0.5 W	0.5 W	
	Power off		0.5 W	0.5 W	
ftware mpatibility	SuperSign CMS		Yes	Yes	
	SuperSign CiviS SuperSign Control / Control+		Yes	Yes	
	SuperSign White Balance		Yes (Sensor requried)	Yes (Sensor requried)	
	Signage 365 Care		Yes Yes Yes		
	Accessories		Remote Controller(include battery 2ea), Power Cord, QSG, DP Cable(1.8M), Regulation Bool Phone to RS232C Gender		
ssories &			3 Year Limited	3 Year Limited	
r	Warranty			3 real Littliceu	
	UPC		7 19192 62493 1		

ttp://www.lg.com/us/business/commercial-display

http://www.twitter.com/LGCommDisplays

1 http://www.facebook.com/LGcommercialdisplays

in http://www.linkedin.com/company/lg-commercial-displays-usa

http://www.youtube.com/lgcommercialdisplayusa

LG may make changes to specifications and product descriptions without notice. For more detailed information on product specifications, please go to the appropriate product information page on https://www.lg.com/us/business. © Copyright 2019 LG Electronics USA, Inc. All rights reserved. LG and the LG logo are registered trademarks of LG Corp. SPEC\_UM3E\_091921\_LR

